

SOLIBRO

PACKAGING AND TRANSPORT INFORMATION

Solibro Solar Modules SL2 and SL2-F



KEEP DRY

THIS
SIDE UP





DO NOT
STEP ON


DO NOT STACK
MORE THAN 2
FOR TRANSPORT

RI

PACKAGING AND TRANSPORT INFORMATION

SOLIBRO SL2 THIN-FILM SOLAR MODULES

| SCOPE OF DELIVERY | | |
|--|--|--|
| Scope of delivery | <ul style="list-style-type: none"> ▪ Solar modules in Box (as described below) ▪ 1× packing list with Module ID numbers on each box ▪ 1× delivery receipt with specifications of handling unit numbers (box IDs) ▪ 1× safety information <p>Measured module current-voltage parameters (“flasher list”) are sent parallel to the delivery per email.</p> | |
| Handling units | The smallest handling unit is a completely filled transport box, as described below. A partially filled transport box will only be sent in special cases after prior agreement (may involve additional cost). | |
| TYPE OF MODULE | | |
| Module | SL2 (UNFRAMED) | SL2-F (FRAMED) |
| Box type | Cardboard container with comb system on a wooden pallet | |
| Measurements (incl. pallet) | L 1,313 mm × W 1,131 mm × H 1,016 mm | L 1,313 mm × W 1,131 mm × H 996 mm |
| Approx. empty weight | ca. 44 kg | ca. 40 kg |
| Box outside view |  |  |
| Box inside view of framed and unframed modules |  |  |
| Modules per box | 44 | 30 |
| Approx. gross weight (full box) | 770 kg | 585 kg |
| Handling of cargo | Max. 2 | |
| Maximum no. of stacked boxes for transport | 1 on 1 (batch of 2) | |
| Maximum no. of stacked boxes for storage | 2 on 1 (batch of 3) | 2 on 1 (batch of 3) |

| LOADING | | |
|---|---|---|
| Module | SL2 (UNFRAMED) | SL2-F (FRAMED) |
| Box type | Cardboard container with comb system on a wooden palette | |
| Max. lorry loading (24 Tons) Inner dimensions: 13.6 × 2.4 × 2.2 m ³ | Max. 30 boxes / max. 1,320 modules Maximum allowed weight (2 × 8 + 2 × 7) | Max. 40 boxes / max. 1,200 modules Maximum allowed volume (2 × 10 + 2 × 10) |
| Max. 20-foot-containerload (24 Tons) Inner dimensions: 5.89 × 2.35 × 2.39 m ³ | Max. 16 boxes / max. 704 modules Maximum allowed volume (2 × 4 + 2 × 4) | Max. 16 boxes / max. 480 modules Maximum allowed volume (2 × 4 + 2 × 4) |
| Max. 40-foot-containerload (24 Tons) Inner dimensions: 12.02 × 2.35 × 2.39 m ³ | Max. 30 boxes / max. 1,320 modules Maximum allowed weight (2 × 8 + 2 × 7) | Max. 34 boxes / max. 1,020 modules Maximum allowed volume (2 × 9 + 2 × 8) |
| Lorry specifications and transit support |  | <p>Solibro conducts pre-delivery check of all lorries. Generally, only lorries are approved for loading which are roadworthy and ready for operation. Solibro loads, stores and fastens the goods safe for transport. The carrier must approve of the safe storage.</p> <p>The load securing complies to the state of the art in accordance with the respective legal regulations (e.g. Road Traffic Act). The carrier must provide appropriate tools for securing the load. Lorries without appropriate equipment to secure the load will not be loaded and will be prohibited to transport the modules. For ecological reasons, Solibro always aspires a complete loading of the lorry.</p> |